

**Amendments to the Claims:**

1. (Currently amended) A method of operating a wireless receiver, comprising the steps of:  
receiving a wireless communicated signal, wherein the wireless communicated signal comprises a first synchronization channel component;

correlating a synchronization channel value to the wireless communicated signal to produce a plurality of correlation samples in response to a correlation between the synchronization channel value and the wireless communicated signal;

comparing the plurality of correlation samples to a threshold;

storing as a first set of correlation samples selected ones of the plurality of correlation samples that exceed the threshold and are within a first time sample period and not storing other correlation samples that do not exceed the threshold and are within the first time sample period, wherein each of the correlation samples in the first set has a corresponding sample time relative to the first time sample period; and

combining a second set of correlation samples with the first set of correlation samples to form an average sample set and further comprising combining additional sets of correlation samples with the average sample set, wherein each of the additional set of correlation samples has a corresponding sample time; and

wherein the combining step comprises combining each sample in each of said additional set of correlation samples with a respective sample in the average sample set such that each combined sample has a like sample time relative to the first time sample period.

2. (Original) The method of claim 1:

wherein the second set of correlation samples are within a second time sample period;  
wherein each of the correlation samples in the second set has a corresponding sample time relative to the second time sample period; and

wherein the combining step comprises combining each sample in the second set of correlation samples with a respective sample in the first set of correlation samples such that each combined sample has a like sample time relative to the first and second time sample period.

3. (Previously amended) The method of claim 2:
  - wherein the wireless communicated signal comprises a plurality of time slots, and
  - wherein each of the plurality of time slots comprises the first synchronization channel component; and
  - wherein each of the first time sample period and the second time sample period has a duration equal to each of the plurality of time slots.
4. (Previously amended) The method of claim 3:
  - wherein the plurality of correlation samples consists of an integer number N correlation samples;
  - wherein the selected ones of the plurality of correlation samples that exceed the threshold consist of an integer number M selected ones of the plurality of correlation samples; and
  - wherein the threshold is at a level such that the integer number M is approximately one-half of the integer number N.
5. (Previously amended) The method of claim 3:
  - wherein the plurality of correlation samples consists of an integer number N correlation samples;
  - wherein the selected ones of the plurality of correlation samples that exceed the threshold consist of an integer number M selected ones of the plurality of correlation samples; and
  - wherein the threshold is at a level such that the integer number M is approximately one-tenth of the integer number N.
6. (Previously amended) The method of claim 1:
  - wherein the plurality of correlation samples consists of an integer number N correlation samples;

wherein the selected ones of the plurality of correlation samples that exceed the threshold consist of an integer number  $M$  selected ones of the plurality of correlation samples; and

wherein the threshold is at a level such that the integer number  $M$  is approximately one-half of the integer number  $N$ .

7. (Previously amended) The method of claim 1:

wherein the plurality of correlation samples consists of an integer number  $N$  correlation samples;

wherein the selected ones of the plurality of correlation samples that exceed the threshold consist of an integer number  $M$  selected ones of the plurality of correlation samples; and

wherein the threshold is at a level such that the integer number  $M$  is approximately one-tenth of the integer number  $N$ .

8. (Previously amended) The method of claim 1:

wherein the plurality of correlation samples consists of an integer number  $N$  correlation samples;

wherein the selected ones of the plurality of correlation samples that exceed the threshold consist of an integer number  $M$  selected ones of the plurality of correlation samples; and

wherein the threshold is at a level such that the integer number  $M$  is less than the integer number  $N$ .

9. (Original) The method of claim 1 wherein the step of combining comprises forming a sum by adding the first set to the second set.

10. (Previously amended) The method of claim 9 wherein the step of combining further comprises dividing the sum by two.

11. (Original) The method of claim 1 wherein the step of combining comprises forming a scaled average with the first set and the second set.
12. (Original) The method of claim 1 wherein the step of combining comprises forming a single pole average with the first set and the second set.
13. (Previously amended) The method of claim 1 wherein each of the plurality of correlation samples comprises an energy measure of a result of the step of correlating a first synchronization channel value to the wireless communicated signal.
14. (Original) The method of claim 1:  
wherein the step of combining a second set of correlation samples with the first set of correlation samples produces a plurality of combined samples; and  
further comprising the steps of:  
determining a peak value in the plurality of combined samples; and  
determining a time position of the peak value.
15. (Currently amended) A method of operating a wireless receiver, comprising the steps of:  
The method of claim 14:  
receiving a wireless communicated signal, wherein the wireless communicated signal comprises a first synchronization channel component;  
correlating a synchronization channel value to the wireless communicated signal to produce a plurality of correlation samples in response to a correlation between the synchronization channel value and the wireless communicated signal;  
comparing the plurality of correlation samples to a threshold;  
storing as a first set of correlation samples selected ones of the plurality of correlation samples that exceed the threshold and are within a first time sample period and not storing other correlation samples that do not exceed the threshold and are within the first time sample period, wherein each of the correlation samples in the first set has a corresponding sample time relative to the first time sample period;

combining a second set of correlation samples with the first set of correlation samples to produce a plurality of combined samples;

determining a peak value in the plurality of combined samples;

determining a time position of the peak value;

wherein the wireless communicated signal further comprises a secondary synchronization channel component; and

further comprising, in response to the time position of the peak value, the step of correlating a plurality of comma free codes with the secondary synchronization code component.

16. (Original) The method of claim 1 wherein the wireless receiver comprises a user station wireless receiver.

17. (Original) The method of claim 1 wherein the step of receiving a wireless communicated signal comprises receiving a CDMA TDD wireless communicated signal.

18. (Original) The method of claim 1 wherein the step of receiving a wireless communicated signal comprises receiving a CDMA FDD wireless communicated signal.

19. (Previously amended) The method of claim 1 and further comprising the steps of: measuring a level of noise in the wireless communicated signal; and setting the threshold in response to the level of noise.

20. (Original) The method of claim 1:  
wherein the second set of correlation samples are within a second time sample period;  
wherein each of the correlation samples in the second set has a corresponding sample time relative to the second time sample period;  
wherein the combining step produces a plurality of combined samples and comprises combining each sample in the second set of correlation samples with a respective sample in the

first set of correlation samples such that each combined sample has a like sample time relative to the first and second time sample period; and

further comprising the steps of:

determining a peak value in the plurality of combined samples; and

determining a time position of the peak value.

21. (Previously amended) The method of claim 20:

wherein the wireless communicated signal further comprises a secondary synchronization channel component; and

further comprising, in response to the time position of the peak value, the step of acquiring the secondary synchronization channel component.

22. (Original) The method of claim 1:

wherein the threshold comprises a first threshold;

wherein the second set of correlation samples are within a second time sample period;

wherein each of the correlation samples in the second set has a corresponding sample time relative to the second time sample period;

wherein the combining step comprises combining each sample in the second set of correlation samples with a respective sample in the first set of correlation samples such that each combined sample has a like sample time relative to the first and second time sample period; and

further comprising the steps of:

forming an average sample set by comparing each of the plurality of combined samples to a second threshold, wherein the second threshold is different than the first threshold;

determining a peak value in the average sample set; and

determining a time position of the peak value.

23. (Cancelled)

24. (Currently amended) The method of claim 23 1 and further comprising, after each step of combining an additional set of correlation samples with the average sample set, the steps of:  
comparing each sample in the average sample set with a corresponding threshold and  
storing those samples in the average sample set that exceed the corresponding threshold;  
determining a peak value among the stored samples; and  
determining a time position of the peak value.
25. (Original) The method of claim 1 and further comprising storing a sample time position for each sample in the first set of correlation samples.
26. (Original) The method of claim 25:  
wherein the second set of correlation samples are within a second time sample period;  
wherein each of the correlation samples in the second set has a corresponding sample time relative to the second time sample period; and  
wherein the combining step comprises, in response to the stored sample time positions, combining each sample in the second set of correlation samples with a respective sample in the first set of correlation samples such that each combined sample has a like sample time relative to the first and second time sample period.
27. (Original) The method of claim 26:  
wherein the threshold comprises a first threshold;  
and further comprising the step of storing additional time positions for any sample correlations in the second time sample period that exceed a second threshold, wherein the second threshold differs from the first threshold.
28. (Currently amended) A wireless receiver, comprising:  
circuitry for receiving a wireless communicated signal, wherein the wireless communicated signal comprises a first synchronization channel component and a second synchronization channel component;

circuitry for correlating a synchronization channel value to the wireless communicated signal to produce a plurality of correlation samples in response to a correlation between the synchronization channel value and the wireless communicated signal;

circuitry for comparing the plurality of correlation samples to a threshold;

circuitry for storing as a first set of correlation samples selected ones of the plurality of correlation samples that exceed the threshold and are within a first time sample period and not storing other correlation samples that do not exceed the threshold and are within the first time sample period, wherein each of the correlation samples in the first set has a corresponding sample time relative to the first time sample period; and

circuitry for combining a second set of correlation samples with the first set of correlation samples to produce a plurality of combined samples;

circuitry for determining a peak value in the plurality of combined samples;

circuitry for determining a time position of the peak value;

wherein the wireless communicated signal further comprises a secondary synchronization channel component; and

further comprising, in response to the time position of the peak value, circuitry for correlating a plurality of comma free codes with the secondary synchronization channel component.

29. (Previously amended) The wireless receiver of claim 28:

wherein the second set of correlation samples are within a second time sample period;

wherein each of the correlation samples in the second set has a corresponding sample time relative to the second time sample period; and

wherein the circuitry for combining comprises circuitry for combining each sample in the second set of correlation samples with a respective sample in the first set of correlation samples such that each combined sample has a like sample time relative to the first and second time sample period.



30. (Previously amended) The wireless receiver of claim 29:  
wherein the wireless communicated signal comprises a plurality of time slots, and  
wherein each of the plurality of time slots comprises the first synchronization channel  
component; and  
wherein each of the first time sample period and the second time sample period has a  
duration equal to each of the plurality of time slots.
31. (Previously amended) The wireless receiver of claim 28 wherein the circuitry for  
combining comprises circuitry for forming a sum by adding the first set to the second set.
32. (Previously amended) The wireless receiver of claim 31 wherein the circuitry for  
combining further comprises circuitry for dividing the sum by two.
33. (Previously amended) The wireless receiver of claim 28 wherein the circuitry for  
combining comprises circuitry for forming a scaled average with the first set and the second set.
34. (Previously amended) The wireless receiver of claim 28 wherein the circuitry for  
combining comprises circuitry for forming a single pole average with the first set and the  
second set.
35. (Previously amended) The wireless receiver of claim 28 wherein each of the plurality of  
correlation samples comprises an energy measure of a result of the step of correlating a first  
synchronization channel value to the wireless communicated signal.
36. (Cancelled)
37. (Cancelled)